



Features :

- ◆ True RMS measurement
- ◆ Primary Current: AC 5~600A
- ◆ Hole Size: 10~50 mm
- ◆ Open angle: 180 degree
- ◆ Easy Installation
- ◆ High Accuracy: 0.5% F.S

Model :

CTSA-□□ (Number means the hole size)

- 10 (Hole Size: 10mm diameter)
- 16 (Hole Size: 16mm diameter)
- 24 (Hole Size: 24mm diameter)
- 36 (Hole Size: 36mm diameter)

Specifications :

- ◆ Primary Current: 5~600Aac
- ◆ Secondary Current: 1.66~120mA
- ◆ Accuracy: 0.5%
- ◆ Operating Condition: -15°C to +50°C
- ◆ Insulation Resistance: 100 MOhms @500Vdc
- ◆ Dielectric Strength: 2500Vac/min
- ◆ Frequency: 45-400 Hz

Model	Primary / Secondary Current	Turns Ratio	Accuracy	OD / ID / HT mm
CTSA-10	5A / 1.66mA	3000:1	0.5%	23 x 40 / 10 / 26
	30A / 15mA	3000:1	0.5%	
	50A / 16.6mA	3000:1	0.5%	
	60A / 20mA	3000:1	0.5%	
CTSA-16	50A / 16.6mA	3000:1	0.5%	30 x 47 / 16 / 32
	60A / 20mA	3000:1	0.5%	
	80A / 26.6mA	3000:1	0.5%	
	100A / 33.3mA	3000:1	0.5%	
CTSA-24	100A / 33.3mA	3000:1	0.5%	55 x 71 / 24 / 51
	150A / 50mA	3000:1	0.5%	
	200A / 66.6mA	3000:1	0.5%	
	300A / 100mA	3000:1	0.5%	
CTSA-36	200A / 100mA	2000:1	0.5%	66 x 94 / 36 / 48
	300A / 100mA	3000:1	0.5%	
	400A / 100mA	4000:1	0.5%	
	600A / 120mA	5000:1	0.5%	